



Thank you for purchasing Happy Trails products. Our products are proudly hand made in Boise Idaho, USA. If you have any questions or concerns about the installation of this product, please contact us directly at 1-800-444-8770 or e-mail installation@happy-trail.com.

Before you begin, place the bike on a hard level surface where you have room to work. Lay out the parts included in this kit and compare to the parts list of these instructions. If any parts or hardware are missing, contact us immediately at the number listed above.

When installing HT guards and racks, **leave all bolts loose until entire rack is fitted.** This allows the rack to move and take up differences in frame construction.

We also recommend that removable strength thread locking compound be used



Note Pictures are of SU rack which is the same installation as this SL rack, except there is no rear support bumper to install.

Installation:

Remove the upper passenger peg bracket mounting bolt. Remove the turn signals, taking care not to damage wires.

Mount the SL racks one side at a time starting with the top mount. Thread in the M6x75 bolt through the SL rack and the turn signal relocation tab. **Use this tab ONLY if Happy Trails top rack is not installed.**

Start the M8x50 bolts at the upper foot peg bracket.

Install the turn signals onto the relocation tab using M8x25 bolts, M8 flat washers and Nylock nuts. The wires may need to be lengthened. **If a top rack is used, mount the turn signals directly in the holes provided in the tail rack side arms, first removing the OEM tabs from the turn signal.**



<u>Bolt List:</u>			
2	M8x50 SHCS	2	M8x25 SHCS
2	M6x75 SHCS	2	Short turn signal tabs (5 inch flat)
2	M6 Flat Washers		
4	M8 Flat Washers		
2	8mm Nylock nuts		